

SO-LOW STABILITY CHAMBER MODEL SCN4-52

49 Cubic Ft. Upright – Temperature Range: 4°C to 70°C / Solid Doors

Specifications:

* Capacity	49 cubic ft.
* Temperature Range	4°C to 70°C
* Dimensions	
* Exterior w x d x h	54" x 35.875" x 81.5"
* Interior w x d x h	49" x 25.5" x 59"

Features:

- Solid Doors
- Casters
- Controller Information:
- Proportional integral derivative (PID) controller with graphic display
- Programmable ramp and soak
- Process phase graphic animations
- USB data port
- RS-485 communication (MODBUS-RTU)
- Real time clock
- Battery backup
- Event logs: 100
- Visual alarm indicator
- Audible alarm indicator
- Process phase specific temp alarm
- Power failure alarm
- Sensor failure alarm
- Designed for pharmaceutical, biological research, Stability, shelf-life testing, plant growth
- Ducted airflow and plenum system optimize air flow and Ensure tight temperature uniformity.
- Control accuracies of 0.1°C control with +/-0.5°C uniformity
- User friendly Programmable Logic Microprocessor control
- Stainless Steel Interior standard
- White Painted Exterior
- Shipping Weight - 560 lbs.
- 115/60/1 12 Amps, 1/3 HP
- Warranty-(Domestic)
1 ½ years parts and labor.
Compressors additional 3 ½ years, no labor.

Specifications subject to change without notice

