

## *SO-LOW EXPLOSION PROOF FREEZER MODEL DHH20-30SDFX MANUAL DEFROST*

*Meets NFPA and OSHA guidelines for Hazardous Locations, Class 1, Division II, Group C & D.*

### **30 Cubic Ft. Upright to -25°C / Solid Door**

#### **Specifications:**

* Capacity	30 cubic ft. / 849 liters
* Temperature	-18°C to -25°C
* Dimensions	
* Exterior w x d x h	35 ¾" x 35" x 77 ½" 90.81 x 88.9 x 196.85 (cm)
* Interior w x d x h	32" x 22.5" x 65" 81.28 x 57.15 x 165.1 (cm)

#### **Features:**

*Thermostat	Exterior Adjustable Mechanical
*Doors	Sealed in UL X-Proof Box
*Legs	Single solid – key lock
*Shelves	Four leveling
*Interior Lighting	4 fixed
*Insulation:	None
*Refrigerant:	Polyurethane foam
*Compressor	R-404A
*Air Circulation	1/3 hp
*Evaporator	Gravity
*Defrost	Hot wall
*Voltage	Manual
*Running Amps	120 VAC
*Supply Plug	6
*Shipping weight	None / Unit must be hardwired
*Approvals	378 lbs.
*Warranty-(Domestic)	UL Listed
	One year parts and labor.

